

19 inch format

Pneumatic unit

PE-L14126

The pneumatic unit from Löhnert Elektronik enables the pneumatic supply to be integrated into a 19 inch cabinet. The pneumatic unit can also be used in ESD areas due to its ESD coating.

There is a pressure indicator, a pressure control valve and a lockable on/off valve on the front panel. The pressure indicator has an additional threshold value display, which can also be queried via the electrical connection on the rear panel.

The rear panel of the pneumatic field has an infeed and several outputs with reduced and non-reduced compressed air. The electrical connections for the pressure indicator and the optional electrical on/off valve are also situated here.



Product information

Technical data

Housing:	19 inch format 2 rack height units 271mm deep handle, colourless, anodised
Paint:	Front panel with ESD coating RAL 7035 light grey
Infeed:	1 x NK 7.2 Compressed air connection oil-free air min. 6bar
Outputs:	reduced 1 x 6mm, 2 x 8mm (outer diameter) non-reduced: 1x 8mm (outer diameter)
El. connections:	Pressure indicator - M12 round plug, 4-pin el. on/off valve - type C
Pressure display:	min./max. Threshold value via 24V signal possible
Components:	Pressure indicator, pressure reducer, manual on/off valve (lockable)
Optional:	electrical on/off valve

Order number code

L14126.58.01.00 - without electrical on/off valve

L14126.58.01.01 - with electrical on/off valve